

25 L9 1A
29-Oct-03

95

INTELLISENSE, Folsom, CA 95630**Combination Infrared/Microwave Intrusion Detection Units:**

Models 8110S, 8120S and 8140S, Input: 7 V dc (minimum), 14 V dc (maximum), 35 mA (10 V dc). Alarm and trouble contacts: 30 V dc, 1.0 A resistive. Tamper contacts: 30 V dc, 50 mA resistive.

Model 8250S, Input: 12 V dc (minimum), 14 V dc (maximum), 35 mA (12 V dc). Alarm and trouble contacts: 30 V dc, 1.0 A resistive. Tamper contacts: 30 V dc, 25 mA resistive.

Model 8660S, Input: 9 V dc (minimum), 14 V dc (maximum), 35 mA (12 V dc). Alarm and trouble contacts: 30 V dc, 1.0 A resistive. Tamper contacts: 30 V dc, 25 mA resistive.

Models DT-420C, DT-435C, DT-435TC, DT-450C and DT-450TC, Input: 12 V dc (minimum), 14 V dc (maximum), 35 mA (12 V dc). Alarm contacts: 30 V dc, 0.5 A resistive (Form C). Tamper contacts: 30 V dc, 25 mA resistive.

Model DT-435TB, Input: 8.5-16 V dc, 35 mA @ 12 V dc. Alarm contacts: 30 V dc, 0.1 A resistive.

Models DT-440SC and DT-460SC, Input: 12 V dc (minimum), 14 V dc (maximum), 41 mA maximum. Alarm contacts: 30 V dc, 0.5 A resistive. Tamper contacts: 30 V dc, 25 mA resistive.

Models DT-500 and DT-500T, Input: 10-14 V dc, 35 mA @ 12 V dc. Alarm contacts: 30 V dc, 100 mA resistive. Tamper contacts: 30 V dc, 25 mA for Model DT-500T only.

Models DT-625S, DT-640ST and DT-625S-ADT, Input: 10-12.9 V dc, 35 mA @ 12 V dc. Alarm contacts: 30 V dc, 100 mA. Tamper contacts (DT-640ST only): 30 V dc, 25 mA.

Models DT-640STC, DT-660STC, DT-6100STC and DT-640STC-ADT, Input: 10-12.9 V dc, 35 mA @ 12 V dc. Alarm contacts: 25 V dc, 125 mA. Tamper contacts: 30 V dc, 25 mA.

Models DT-735 and DT-750 Input: 10-14 V dc, 35 mA @ 12 V dc. Alarm contacts: 30 V dc, 100 mA. Tamper contacts: 30 V dc, 25 mA.

Models DT-900, DT-901, DT-906 and DT-907, Input: 10-15 V dc, 21 mA @ 12 V dc. Alarm contacts: 25 V dc, 125 mA. Tamper contacts: 30 V dc, 25 mA.

Models MC-760, MC-760T and MC-760/ADT, Input: 9.5-14 V dc, 10 mA @ 12 V dc. Alarm contacts: 30 V dc, 100 mA.

Glass Break Detection Units -

Model FG-730, Input: 8.5 V dc (minimum), 16 V dc (maximum), 25 mA (12 V dc). Alarm contacts: 30 V dc, 0.5 A resistive. Tamper contacts: 30 V dc, 50 mA resistive.

Models FG-1008, FG-1508, FG-1608 and FG-1608B, both with magnetic contacts, Input: 12 V dc, 30 mA (maximum). Alarm contacts: 25 V dc, 250 mA (maximum). Tamper contacts: 24 V dc, 25 mA.

Models FG-1015C, FG-1025FC, FG-1025FDC, FG-1025RC and FG-1025ZC, Input: 12 V dc, 35 mA (maximum). Alarm contacts: 25 V dc, 125 mA (maximum). Tamper contacts: 24 V dc, 25 mA.

Models FG-1515, FG-1525, FG-1525R, FG-1615 and FG-1625, Input: 6 V dc (minimum), 18 V dc (maximum), 22 mA maximum (12 V dc). Alarm contacts, Form "A": 25 V dc, 125 mA.

Models FG-1525F, FG-1525FD and FG-1625F, Input: 6 V dc (minimum), 18 V dc (maximum), 22 mA maximum (12 V dc). Alarm contacts, Form "A": 25 V dc, 125 mA.

Models FG-1515T, FG-1525RT, FG-1525T, FG-1615T, FG-1625R, FG-1625RT and FG-1625T, Input: 6 V dc (minimum), 18 V dc (maximum), 22 mA maximum (12 V dc). Alarm contacts, Form "C": 25 V dc, 125 mA. Tamper contacts: 24 V dc, 25 mA.

Model 9500SN, Input: 8-11 V P/P from control unit polling loop, 4 mA in alarm condition (LED enabled).

Models FG-1625SN, FG-1625SN-ADT, Input: 8.06 V dc supplied from control unit polling loop, 5.0 mA maximum.

Ceiling Mounted Motion Detector -

Model DT-5360, Input: 8.5 V dc (minimum), 16 V dc (maximum), 40 mA (12 V dc). Alarm contacts: 30 V dc, 0.5 A resistive. Tamper contacts: 30 V dc, 25 mA resistive. Models DT-6360STC and DT-6360STC-ADT, Input: 10 V dc (minimum), 12.9 V dc (maximum), 50 mA. Alarm contacts, Form "C" (NC): 25 V dc, 125 mA resistive. Tamper contacts, Form "A" (NC): 30 V dc, 25 mA resistive.

Infrared Type:

Models IS-150, MC-135 and MC-550, Input: 10-14 V dc, 100 mA (maximum). Alarm contacts, Form "A": 24 V dc, 100 mA resistive.

Models IS-150T and MC-550T, Input: 10-14 V dc, 100 mA (maximum). Alarm contacts, Form "A": 24 V dc, 100 mA resistive. Tamper contacts, Form "A" (NC): 24 V dc, 25 mA resistive.

Models DT-700 and DT-706, Input: 9-14.5 V dc, 25 mA @ 12 V dc. Alarm contacts, Form "A": 30 V dc, 500 mA resistive. Tamper contacts, Form "A" (NC): 24 V dc, 50 mA resistive. Model DT-706C, Input: 9-14.5 V dc, 25 mA @ 12 V dc. Alarm contacts, Form "C": 30 V dc, 500 mA resistive. Tamper contacts, Form "A" (NC): 24 V dc, 50 mA resistive.

Marking: ULC Integral Marker consisting of ULC in a circle.

Instruction Detection Units
C BP 369

25 L30

INTELLISENSE, Folsom, CA 95630

Magnetically actuated contact for closed loop circuits, indoor and outdoor applications, Models MPS-9WG, MPS-20WG, MPS-45WG, MPS-A10, MPS-A30, MPS-A30C, MPS-5, MPS-60, MPS-70WG and MPS-80WG. Contact rating: 30 V ac/dc, 3(A) mA.

Magnetically actuated contact, overhead door type, Models MPS-50C, RS-51B and MPS-A51C. Contact rating: 30 V ac/dc, 300 mA.

contacts = switches
CBP 575