

# Performance Series Cameras



EXPANDING OUR CAMERA PORTFOLIO  
TO MEET YOUR EVERY NEED

**Because performance matters**

## **Honeywell Security**

Honeywell House  
Bekker Street, Truer Close  
Waterfall Park  
Midrand 1685  
South Africa  
Tel: +27 (11) 695 8016  
Fax: +27 (11) 315 2198  
[www.honeywell.com/security/za](http://www.honeywell.com/security/za)

HVS-PERF-RSA-01(0608)BR-COE  
June 2008  
© 2008 Honeywell International Inc.

**Honeywell**

**Honeywell**

# Introducing Honeywell's new Performance Series Cameras

## Because performance matters

No matter what performance you need in a camera, we've got the options you're looking for. Now we're enhancing our camera portfolio with a variety of indoor, outdoor and low light cameras that let you pick the perfect camera for your application. The Performance Series of cameras includes a wide range of high performing IR bullet cameras and mini-domes that are easy to install and even easier to use. These cameras offer sharper image quality so you see every detail when it counts. Plus, our cameras are competitively priced—giving you value from a partner you know and trust.

Honeywell's experience and commitment to innovation, combined with the quality and reliability of our integrated video systems, allows our customers to meet their existing and emerging security challenges. Whether you need the performance of IR illumination for low light environments or basic functionality for indoor or outdoor applications, Honeywell has a performer for you!

Our Performance Series offers:

- IR Bullet Cameras
- IR Indoor/Outdoor Mini-domes
- IR Indoor Mini-domes
- Indoor/Outdoor Mini-domes
- Indoor Mini-domes



	Bullet Cameras			Mini-Domes						
Style	IR Bullet Cameras			IR Indoor/Outdoor Mini-Domes (Impact Resistant)		IR Indoor Mini-Domes		Indoor/Outdoor Mini-Domes (Impact Resistant)		Indoor Mini-Domes
Honeywell Part #	HB73SX	HB72SX <small>(Available soon, please consult us)</small>	HB70X	HD73X <small>(Available soon, please consult us)</small>	HD70X	HD61X <small>(Available soon, please consult us)</small>	HD60X	HD51X	HD50X <small>(Available soon, please consult us)</small>	HD40X <small>(Available soon, please consult us)</small>
Description	Super High Res True Day/Night	Super High Res Day/Night	Standard Res Day/Night	Super High Res Day/Night	Super High Res Day/Night	Standard Res Day/Night	Standard Res Day/Night	Super High Res Colour	Super High Res Colour	Standard Res Colour
Image Sensor	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD
Horizontal Resolution	550 TVL	530 TVL	380 TVL	530 TVL	550 TVL	380 TVL	380 TVL	550 TVL	530 TVL	380 TVL
S/N Ratio	> 50 dB (AGC Off)	> 48 dB (AGC Off)	> 48 dB (AGC Off)	> 48 dB (AGC Off)	> 50 dB (AGC Off)	> 48 dB (AGC Off)	> 48 dB (AGC Off)	> 50 dB (AGC Off)	> 48 dB (AGC Off)	> 48 dB (AGC Off)
Lens	DC Iris Vari-focal Lens (f=3.8-9.5 mm)	Fixed Lens (f=4.0 mm)	Fixed Lens (f=4.3 mm)	DC Iris Vari-focal Lens (f=3.8-9.5 mm)	Fixed Lens (f=4.0 mm)	Manual Vari-focal Lens (f=4-9 mm)	Fixed Lens (f=4.0 mm)	DC Iris Vari-focal Lens (f=4-9 mm)	Fixed Lens (f=3.8 mm)	Fixed Lens (f=3.8 mm)
Min. Illumination	Day (0.3 lux), Night (0.00 lux, IR LED On)	Day (0.3 lux), Night (0.00 lux, IR LED On)	Day (0.1 lux), Night (0.00 lux, IR LED On)	Day (0.3 lux), Night (0.00 lux, IR LED On)	Day (0.3 lux), Night (0.00 lux, IR LED On)	Day (0.3 lux), Night (0.00 lux, IR LED On)	Day (0.1 lux), Night (0.00 lux, IR LED On)	0.3 lux	0.3 lux	0.1 lux
Illumination	18 IR LED (850 nm, 30°)	12 IR LED (850 nm, 30°)	12 IR LED (850 nm, 30°)	20 IR LED (850 nm, 30°)	24 IR LED (850 nm, 30°)	20 IR LED (850 nm, 30°)	24 IR LED (850 nm, 30°)			
IR LED Visible Range	Max. 65 ft., 20m	Max. 50 ft., 15m	Max. 50 ft., 15m	Max. 65 ft., 20m	Max. 50 ft., 15m	Max. 65 ft., 20m	Max. 50 ft., 15m			
OSD				Yes		Yes				
Privacy Zone				On/Off (4 Programmable Zones)		On/Off (4 Programmable Zones)				
Motion Detection				On/Off (64 Programmable Zones)		On/Off (64 Programmable Zones)				
Input Voltage	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Power Consumption	Max. 3.6 W/300mA	Max. 3.6 W/300mA	Max. 3.6 W/300mA	Max. 4.5 W/360mA	Max. 5 W/400mA	Max. 4.5 W/360mA	Max. 5 W/400mA	Max. 3 W/250mA	Max. 1.8 W/150mA	Max. 1.8 W/150mA

Power Supply  
12VDC, EU Plug

**PSU-PER12VDC-EU**

Get your Performance Series cameras today! To order or for more information, contact your local ADI-GARDINER branch or call 0 11 574 2500