


Flexible Galaxy control panel  
range for small to medium sized  
security installations

Comparison chart



<b>G2 vs. Galaxy Dimension vs. Galaxy Flex Features</b>	<b>G2-20*</b>	<b>FX020***</b>	<b>G2-44+*</b>	<b>FX050***</b>	<b>GD48**</b>	<b>FX100***</b>	<b>GD96**</b>
Zones on board (Max expansion) Max wireless zones	12 (20) 20	12 (20) 8	12 (44) 44	12 (52) 40	16 (48) 32	12 (100) 88	16 (96) 80
Wireless transceiver/RF Portal	2	8	2	8	4	8	8
Groups/Areas/Partitions	3+1 common	3	3+1 common	4	8	8	16
Outputs - switched (with trigger module)	4-16 (8)	2-6 (14)	4-28 (8)	2-22 (30)	8-24 (6)	2-46 (54)	8-48 (6)
Trigger outputs - relay	-	-	-	-	1	-	1
Speaker driver	No	Yes					
Integrated PSU	1A	1A	1.4A	1A	2.5A	1A	2.5A
Output current rating (EN50131)	0.6A @ grade 2	0.7A @ grade 2	1A @ grade 2	0.7A @ grade 2	1.2A @ grade 3	0.7A @ grade 2	1.2A @ grade 3
Users	24	25	24	50	100	100	250
Event log	384	500	384	500	1000	1000	1500
Access event log	-	500	-	500	500	1000	1000
7 day timer schedules (Autoset & Access)	-	2	-	4	19	4	35
Links	-	5	-	5	64	5	128
Local communication interface	RS232 (with lead)	USB	RS232 (with lead)	USB	RS232	USB	RS232
PSTN	Onboard	Onboard	Onboard	Onboard	Onboard	Onboard	Onboard
Ethernet	Optional	Optional	Optional	Optional	Optional	Optional	Optional
GSM/GPRS	No	Optional	Optional	Optional	No	Optional	No
Voice listen-in options	-	2 channels	1 channel	2 channels	8 channels	2 channels	16 channels
2-way voice options	No	2 speaker channels	1 speaker channel	2 speaker channels	8 speaker channels	2 speaker channels	16 speaker channels
Keypads (keyprox)	4 (4)	4 (4)	4 (4)	4 (4)	8 (3)	8 (8)	16 (7)
Multi-users	Yes						
Door controllers (DCM)	-	2	-	4	4	4	16
DCM controlled doors	-	4	-	8	8	8	32
Bus mounted prox readers	1	4	1	8	4	8	16
Access control groups (user templates)	-	5	-	10	50	20	50
Galaxy TouchCenter/ prox	-	1	-	1	1	1	2
Approvals	PD6662:2004/ EN50131-1:2006	PD6662:2010/ EN50131-3:2009	PD6662:2004/ EN50131-1:2006	PD6662:2010/ EN50131-3:2009	PD6662:2004/ EN50131-1:2006	PD6662:2010/ EN50131-3:2009	PD6662:2004/ EN50131-1:2006

\*G2      \*\*Galaxy Dimension      \*\*\*Galaxy Flex

T: +44 (0)844 8000 235 F: +44 (0)1698 738 500 E: securitysales@honeywell.com W: www.honeywell.com/security/uk

Flex-01-EN(0711)PC-C